

# Plastiment® SD2

## **Compaction Aid and Strength Enhancer for Cast Stone Production**

### **Technical Data Sheet**

#### **DESCRIPTION**

**Plastiment SD2** is a liquid admixture, which greatly assists compaction and improves the degree of finish achieved on the cast stone production.

#### **USES**

- Contains a compaction aid, bringing a degree of concrete strength impossible to achieve prior to the introduction of this admixture
- ★ Greater degree of cement utilisation ensuring a stronger, more durable artificial stone product
- ★ Appreciably higher strengths, especially in the first 24 hours - possibility to save cement and costs
- ★ Closer textured top and side surfaces and harder arrisses are achieved
- Easier compaction leads to much improved strength attainment characteristics
- \* Extremely economical in use

## **Technical Data (typical)**

Form: Liquid

Colour: Light straw/clear

Specific gravity: 1.01

Dosage % by wt

of cement: 0.4 - 1.0

**Chloride content**Wil (ie less than 0.1% w/w)

Freezing point °C: -1°C

All above values are approximate.



### **ADVANTAGES**

- The concrete's aesthetic quality, strength and durability are all enhanced by the use of Plastiment SD2.
- ★ Because it is in liquid form, **Plastiment SD2** is simple to dispense into the concrete mix.
- ★ Permeability is reduced and waterproofing abilities enhanced.
- ★ Placing of the concrete is easier, minimising the efforts taken to produce an excellent product.

#### **METHOD OF USE**

Plastiment SD2 should be dispensed with the mix water into semi-dry concrete mixes.

#### **PACKAGING**

Plastiment SD2 is supplied in 200 litre drums and in

#### STORAGE AND SHELF LIFE

Plastiment SD2 should be stored in dry conditions above 0°C in original sealed containers.



Handling Precautions

Sika products are generally harmless provided that certain precautions normally taken when handling chemicals are observed. The materials must not, for instance, be allowed to come in contact with foodstuffs or food utensils and measures should also be taken to prevent the uncured materials from coming in contact with the skin, since people with particularly sensitive skin may be affected. The use of protective clothing, goggles, barrier creams and rouber gloves is required. The skin should be thoroughly cleaned at the end of each working period either by washing with soap and warm water or by using a resin-removing cream - the use of powerful solvents is to be avoided. Disposable paper towels - not cloth towels - should be used to dry the skin. Adequate ventilation of the working area is recommended. In case of accidental eye or mouth contact, flush with water - consult a doctor immediately. Health and Safety information on Sika Products is available and we strongly advise that this is read prior to their use. Sika products are for professional use and should be stored in sealed containers away from the reach of children.

Important Note
The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

#### Please consult our Technical Sales Department for further information

SIKA LIMITED

Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ

Tel: 01707 394444 Email: sika@uk.sika.com Fax: 01707 329129 www.sika.com





