

**PRODUCT AND COMPANY IDENTIFICATION**

Product Code SGD551EP
Product Name Sikagard 551S Elastic Primer
Product Description Primer for Sikagard 550W Elastic protective coatings.
Manufacturer/Supplier Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire.
AL7 1BQ
tel. 01707 394444
Fax. 01707 329129

COMPOSITION/INFORMATION ON THE COMPONENTS**Preparation - Hazardous ingredients (Europe)**

Component		Concentration	Classification	Risk Phrases
1) Solvent Naptha (Petroleum),Light Aromatic.	64742-95-6	50.00% - 100.00%	Xn, N	R10, R37, R51/53, R65, R66, R67
2) 1 methoxy-2-propanol	107-98-2	2.50% - 10.00%	-	R10

HAZARD IDENTIFICATION

Main Hazards Flammable.
Irritating to respiratory system.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Repeated exposure may cause skin dryness or cracking
Vapours may cause drowsiness and dizziness

FIRST AID MEASURES

Eye Contact Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open.
Obtain medical attention urgently.

Skin Contact Wash skin thoroughly with soap and water.
Obtain medical attention if blistering occurs or redness persists.
Contaminated clothing should be washed or dry-cleaned before re-use.

Ingestion Do not induce vomiting.
Obtain medical attention.

Inhalation Remove from exposure. Obtain medical attention.

FIRE FIGHTING MEASURES

Extinguishing Media Use foam, dry chemical or carbon dioxide.
Dry sand may be used on small fires.

Special Hazards of Product Combustion will produce smoke,carbon dioxide and carbon monoxide.

Protective Equipment for Fire-Fighting Wear full protective clothing and self-contained breathing apparatus.

**ACCIDENTAL RELEASE MEASURES****Personal Precautions**

Wear appropriate protective clothing. Eliminate all sources of ignition.

**Environmental Precautions and
Clean-up Methods
Spillages**

Try to prevent the material from entering drains or water courses.

Contain and absorb using earth, sand or other inert material.
Transfer into suitable containers for recovery or disposal.

HANDLING AND STORAGE**Handling**

Avoid contact with eyes, skin and clothing.
Exposure by inhalation or skin contact should be minimised by good Industrial Hygiene practices.
Use in well ventilated area.

Storage

Storage area should be: cool. dry. well ventilated. out of direct sunlight.
Store away from sources of heat or ignition.

EXPOSURE CONTROLS/PERSONAL PROTECTION**Occupational Exposure Limits - GB**

1) 1 methoxy-2-propanol

UK EH40: OES 100ppm (375mg/m³) 8h TWA.
UK EH40: OES 150ppm (560mg/m³) 15min STEL

Engineering Control Measures

Use of the basic principles of Industrial Hygiene will enable this material to be used safely.

Respiratory Protection

Adequate ventilation should be provided to maintain solvent concentrations in the workplace below exposure limits.
Respiratory protection if there is a risk of exposure to high vapour concentrations.

Hand Protection

Wear suitable impervious gloves. (butyl / nitrile type)

Eye Protection

Chemical goggles if there is a risk of splashing.

PHYSICAL AND CHEMICAL PROPERTIES**Physical State**

Liquid.

Color

Clear. Yellow.

Odor

Hydrocarbon.

pH

Not applicable.

Flash Point °C

Approx. 33

Solubility - Water

Immiscible.

Density (kg/m³)

Approx. 970 at 20 °C.

Viscosity (at 20°C)

Mobile liquid at ambient temperatures.

STABILITY AND REACTIVITY**Stability**

Stable under normal conditions.

Conditions to avoid

Sources of ignition. High temperatures.

Hazardous Decomposition Products

Combustion will generate: oxides of carbon. acrid smoke and irritating fumes.

**TOXICOLOGICAL INFORMATION**

<i>Acute toxicity</i>	Excessive exposure may produce anaesthetic or narcotic effects.
<i>Eye irritation</i>	Liquid and vapour can cause irritation on contact and at high concentrations.
<i>Skin irritation</i>	Frequent skin contact may cause irritation and defatting due to the solvent content. Repeated exposure may cause skin dryness or cracking.

ECOLOGICAL INFORMATION

<i>Mobility</i>	The product is insoluble in water.
<i>Persistence/degradability</i>	The product is partially or slowly biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.

DISPOSAL

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

TRANSPORT INFORMATION

<i>UN : UN number</i>	1263
<i>UN : Proper shipping name</i>	Paint
<i>UN : Class</i>	3.3
<i>UN : Packing Group</i>	3
<i>ADR/RID Substance Identification Number</i>	1263
<i>ADR/RID Proper shipping name</i>	Paints - flash point between 21°C and 55°C.
<i>ADR/RID Class</i>	3
<i>ADR/RID Item Number</i>	31(c)
<i>ADR/RID Hazard Identification Number</i>	30
<i>IMDG : Proper shipping name</i>	Paint.
<i>IMDG : Packing Group</i>	3
<i>IMDG : Class</i>	3.3
<i>IMDG : Marine Pollutant</i>	P
<i>IMDG : Ems Number</i>	3-05
<i>IATA : Proper shipping name</i>	Paint.
<i>IATA : Packing Group</i>	3
<i>IATA : Class</i>	3

REGULATORY INFORMATION

<i>Label Requirements</i>	Irritant, Dangerous for the environment
---------------------------	---



**SAFETY DATA SHEET****Sikagard 551S Elastic Primer**

Date of issue - 09/04/2002.

SGD551EP

Risk Phrases

Flammable.
Irritating to respiratory system.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Repeated exposure may cause skin dryness or cracking
Vapours may cause drowsiness and dizziness

Safety Phrases

Use only in well-ventilated areas.

OTHER INFORMATION**First Issue Date**

17.11.1994

Revisions Highlighted

Hazards Identification
Exposure controls/personal protection
Regulatory Information

Uses and Restrictions

Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.

UK Legislation

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.
Chemicals (Hazard Information and Packaging) Regulations, 2002.
SI 1999/437: The Control of Substances Hazardous to Health Regulations
SI No. 972/1996: The Special Waste Regulations 1996
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.
Petroleum (Consolidation) Act, 1928 and associated legislation.

UK Guidance Publications

EH40, Occupational Exposure Limits, HSE. Revised Annually.
General Approved Code of Practice to COSHH Regulations, HSE.
HS(G) 53, Respiratory Protective Equipment - a Practical Guide for Users, HSE.
Guide to Highly Flammable Liquids & LPG Regulations - H&SE.

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.