

**1. PRODUCT AND COMPANY IDENTIFICATION**

Product Code	SKFL91A
Product Name	Sikafloor 91 Part A
Product Description	3- component epoxy resin based flooring mortar/screed.
Manufacturer/Supplier	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

2. COMPOSITION/INFORMATION ON THE COMPONENTS**Preparation - Hazardous ingredients (Europe)**

Component	CAS/EINECS	Concentration	Classification	Risk Phrases
Epoxy resin (No.Av. mol.wt. < 700)	25068-38-6	50.00% - 100.00%	Xi, N	R36/38, R43, R51/53
Aliphatic glycidyl ether	68609-97-2	2.50% - 10.00%	Xi, N	R38, R43, R51/53

3. HAZARD IDENTIFICATION

Main Hazards	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
---------------------	---

4. FIRST AID MEASURES

Eye Contact	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention urgently.
Skin Contact	Wipe off as much as possible with a clean dry cloth. Wash skin thoroughly with soap and water. Solvents should not be used to clean skin because they may increase the penetration of the material.
Ingestion	Wash out mouth with water. Obtain medical attention.
Inhalation	Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.

5. FIRE FIGHTING MEASURES

Extinguishing Media	Not readily combustible. Use foam, dry chemical or carbon dioxide.
Extinguishing Media - Not suitable	Do not use water jet.
Special Hazards of Product	Combustion will produce smoke, carbon dioxide and carbon monoxide.
Protective Equipment for Fire-Fighting	Wear full protective clothing and self-contained breathing apparatus.

**6. ACCIDENTAL RELEASE MEASURES**

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

<i>Handling</i>	Exposure by inhalation or skin contact should be minimised by good Industrial Hygiene practices. Avoid contact with eyes, skin and clothing. Use in well ventilated area.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Exposure should be kept as low as reasonably practicable by the application of hygiene principles and appropriate techniques.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Liquid.
<i>Color</i>	Straw - Colourless.
<i>Odor</i>	Faint.
<i>Flash Point °C</i>	Exceeds 100.
<i>Solubility - Water</i>	Immiscible.
<i>Density (kg/m3)</i>	Approx. 1100 at 20 °C.
<i>Viscosity (at 20°C)</i>	Mobile liquid at ambient temperatures.

10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Combustion will generate: oxides of carbon. acrid smoke and irritating fumes.

11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	Irritating to the eyes.
<i>Skin irritation</i>	Frequent or prolonged skin contact may cause some local short term skin irritation.
<i>Sensitization - Skin</i>	The low molecular weight epoxy resin is a potential skin sensitiser. The possibility of allergic sensitisation should be considered

**12. ECOLOGICAL INFORMATION**

<i>Mobility</i>	The product is insoluble in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.


13. DISPOSAL

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

14. TRANSPORT INFORMATION

<i>UN : UN number</i>	3082
<i>UN : Proper shipping name</i>	Environmentally hazardous substances, liquid, n.o.s.
<i>UN : Class</i>	9
<i>UN : Packing Group</i>	3
<i>ADR/RID : Number</i>	3082
<i>ADR/RID : Proper shipping name</i>	Environmentally hazardous substance, liquid, n.o.s. contains Epoxy Resin
<i>ADR/RID : Class</i>	
<i>ADR/RID : Item Number</i>	11 (c)
<i>ADR/RID : Hazard Identification Number</i>	90
<i>IMDG : Proper shipping name</i>	Environmentally hazardous substance, liquid, N.O.S. contains Epoxy Resin
<i>IMDG : Packing Group</i>	3
<i>IMDG : Class</i>	9
<i>IATA : Proper shipping name</i>	Not Classified for Air Transport

15. REGULATORY INFORMATION

<i>Label Requirements</i>	Irritant, Dangerous for the environment 
<i>Risk Phrases</i>	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<i>Safety Phrases</i>	Avoid contact with skin. Wear suitable gloves. Contains epoxy constituents. See information supplied by the manufacturer.



SAFETY DATA SHEET

Sikafloor 91 Part A

Date of issue - 19/06/2002.

SKFL91A

16. OTHER INFORMATION

<i>First Issue Date</i>	22.02.1995
<i>Revisions Highlighted</i>	Hazards Identification Regulatory Information
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.
<i>UK Legislation</i>	Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions. Chemicals (Hazard Information and Packaging) Regulations, 2002. SI 1999/437: The Control of Substances Hazardous to Health Regulations SI No. 972/1996: The Special Waste Regulations 1996 SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.
<i>UK Guidance Publications</i>	Approved Code of Practice - Management of Health and Safety at Work, HSE. General Approved Code of Practice to COSHH Regulations, HSE.
<i>Footnote</i>	The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.

**1. PRODUCT AND COMPANY IDENTIFICATION**

Product Code	SKFL91B
Product Name	Sikafloor 91 Part B
Product Description	3- component epoxy resin based flooring mortar/screed.
Manufacturer/Supplier	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

2. COMPOSITION/INFORMATION ON THE COMPONENTS**Preparation - Hazardous ingredients (Europe)**

Component	CAS/EINECS	Concentration	Classification	Risk Phrases
Benzyl Alcohol	100-51-6	25.00% - 50.00%	Xn	R20/22
Isophoronediamine	2855-13-2	10.00% - 25.00%	C	R21/22, R34, R43, R52/53
M-phenylebis(methylamine)	1477-55-0	10.00% - 25.00%	C	R20/22, R34, R43, R52/53
3,6,9-triazaundecamethylenediamine	112-57-2	2.50% - 10.00%	C, N	R21/22, R34, R43, R51/53
Trimethylhexamethylenediamine (cyanethylated)		2.50% - 10.00%	C	R22, R34, R43
2,4,6-Tri(dimethylaminomethyl) phenol	90-72-2	2.50% - 10.00%	Xn	R22, R36/38
Trimethylhexamethylene diamine	25620-58-0	1.00% - 2.50%	C	R22, R34, R43, R52/53

3. HAZARD IDENTIFICATION

Main Hazards	Causes burns. May cause sensitisation by skin contact. Harmful by inhalation, in contact with skin and if swallowed. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
---------------------	---

4. FIRST AID MEASURES

Eye Contact	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention urgently.
Skin Contact	Wipe off as much as possible with a clean dry cloth. If material proves difficult to remove, use suitable skin cleanser (not solvent). Solvents should not be used to clean skin because they may increase the penetration of the material. Contaminated clothing should be washed or dry-cleaned before re-use.
Ingestion	Do not induce vomiting. Obtain medical attention.
Inhalation	Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.

**5. FIRE FIGHTING MEASURES**

<i>Extinguishing Media</i>	Not readily combustible. Use foam, dry chemical or carbon dioxide.
<i>Extinguishing Media - Not suitable</i>	Do not use water jet.
<i>Special Hazards of Product</i>	Thermal decomposition or burning may release oxides of carbon, nitrogen and other toxic gases and vapours.
<i>Protective Equipment for Fire-Fighting</i>	Wear full protective clothing and self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

<i>Handling</i>	Exposure by inhalation or skin contact should be minimised by good Industrial Hygiene practices. Mix in a well ventilated area. Avoid contact with eyes, skin and clothing.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Liquid.
<i>Color</i>	Amber.
<i>Odor</i>	Amine like.
<i>pH</i>	Approx. 12 in water. (soluble phase)
<i>Flash Point °C</i>	Exceeds 100.
<i>Solubility - Water</i>	Partially soluble.
<i>Density (kg/m³)</i>	Approx. 1020
<i>Viscosity (at 20°C)</i>	Mobile liquid at ambient temperatures.

**10. STABILITY AND REACTIVITY**

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Heating may produce: ammonia. oxides of carbon. oxides of nitrogen. acrid smoke and irritating fumes.

11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	This material is corrosive to the eye.
<i>Skin irritation</i>	Frequent or prolonged skin contact may cause some local short term skin irritation. This material is corrosive to the skin.
<i>Sensitization - Skin</i>	The possibility of allergic sensitisation should be considered

12. ECOLOGICAL INFORMATION

<i>Mobility</i>	The product is sparingly soluble in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.

13. DISPOSAL

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

14. TRANSPORT INFORMATION

<i>UN : UN number</i>	1760
<i>UN : Proper shipping name</i>	Corrosive liquid, n.o.s.
<i>UN : Class</i>	8
<i>UN : Packing Group</i>	3
<i>ADR/RID : Number</i>	1760
<i>ADR/RID : Proper shipping name</i>	Corrosive liquid, n.o.s.
<i>ADR/RID : Class</i>	contains: Isophoronediamine, Xylylenediamine
<i>ADR/RID : Item Number</i>	66(c) Class C9
<i>IMDG : Proper shipping name</i>	Corrosive liquid, N.O.S. contains Isophoronediamine, Xylylenediamine
<i>IMDG : Packing Group</i>	3
<i>IMDG : Class</i>	8
<i>IMDG : Ems Number</i>	8-15; F-A, S-B
<i>IATA : Proper shipping name</i>	Corrosive liquid, N.O.S. contains Isophoronediamine, Xylylenediamine
<i>IATA : Packing Group</i>	3
<i>IATA : Class</i>	8



SAFETY DATA SHEET

Sikafloor 91 Part B

Date of issue - 28/11/2003.

SKFL91B

15. REGULATORY INFORMATION

Label Requirements

Corrosive



Risk Phrases

Causes burns.
May cause sensitisation by skin contact.
Harmful by inhalation, in contact with skin and if swallowed.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrases

Avoid contact with skin.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Wear suitable protective clothing, gloves and eye/face protection.

Contains

Benzyl alcohol
M-phenylebis(methylamine)
3-aminomethyl-3,5,5-trimethylcyclohexylamine
3,6,9-triazaundecamethylenediamine
Trimethylhexane-1,6-diamine

16. OTHER INFORMATION

First Issue Date

22.02.1995

Revisions Highlighted

Composition / information on ingredients
Regulatory Information

Uses and Restrictions

Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.

UK Legislation

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.
SI 2002/1677 Chemicals (Hazard Information and Packaging) Regulations
SI 2002/2677 The Control of Substances Hazardous to Health Regulations
SI No. 972/1996: The Special Waste Regulations 1996
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

UK Guidance Publications

Approved Code of Practice - Management of Health and Safety at Work, HSE.
General Approved Code of Practice to COSHH Regulations, HSE.

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.

**1. PRODUCT AND COMPANY IDENTIFICATION**

<i>Product Code</i>	SKFL91C
<i>Product Name</i>	Sikafloor 91 Part C
<i>Product Description</i>	3- component epoxy resin based flooring mortar/screed.
<i>Manufacturer/Supplier</i>	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

2. COMPOSITION/INFORMATION ON THE COMPONENTSPreparation - Hazardous ingredients (Europe)

<i>Component</i>	<i>CAS/EINECS</i>	<i>Concentration</i>	<i>Classification</i>	<i>Risk Phrases</i>
Barium Sulphate	7727-43-7	1.00% - 2.50%	-	-

3. HAZARD IDENTIFICATION

<i>Main Hazards</i>	Not classified as hazardous. Respirable dusts could if inhaled over a prolonged period constitute a health hazard.
---------------------	---

4. FIRST AID MEASURES

<i>Eye Contact</i>	Wash out eye with plenty of water. Obtain medical attention if soreness or redness persists.
<i>Skin Contact</i>	Wash skin with soap and water.
<i>Ingestion</i>	Wash out mouth with water. Do not induce vomiting. Obtain medical attention.
<i>Inhalation</i>	Remove from exposure.

5. FIRE FIGHTING MEASURES

<i>Extinguishing Media</i>	Not combustible.
<i>Special Hazards of Product</i>	None.

6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Avoid creating a dust. Sweep or preferably vacuum up and collect in suitable containers for recovery or disposal.

**7. HANDLING AND STORAGE**

Handling	Mix in a well ventilated area.
Storage	Avoid inhaling dust. Storage area should be: dry. Store in the original container securely closed .

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Occupational Exposure Limits - GB**

Barium Sulphate	UK EH40: OES 4mg/m ³ 8h TWA. Dust, respirable: UK EH40: OES 10mg/m ³ 8h TWA. Dust, total inhalable:
-----------------	--

Engineering Control Measures	Every effort should be made to prevent airborne dusts arising during mixing operations. Exposure should be kept as low as reasonably practicable by the application of hygiene principles and appropriate techniques.
Respiratory Protection	Good ventilation should be provided to keep airborne dust levels below exposure limits. If limits are exceeded use an approved dust mask.
Hand Protection	Wear suitable impervious gloves.
Eye Protection	Wear safety glasses if risks of accidental contamination are possible during application.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Powder.
Color	Various
Odor	None.
Flash Point °C	Not applicable.
Solubility - Water	Insoluble.
Density (kg/m³)	Approx. 1600 (loose)

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	None known.
Materials to avoid	None known.
Hazardous Decomposition Products	None known.

11. TOXICOLOGICAL INFORMATION

Acute toxicity	Low order of acute toxicity.
Eye irritation	Abrasion will likely cause transient irritation.
Skin irritation	Unlikely to cause irritation from occasional contact



SAFETY DATA SHEET

Sikafloor 91 Part C

Date of issue - 19/06/2002.

SKFL91C

12. ECOLOGICAL INFORMATION

<i>Mobility</i>	The product is insoluble in water.
<i>Persistence/degradability</i>	The product is resistant to biodegradation.

13. DISPOSAL

<i>Product Disposal</i>	Incineration or landfill.
<i>Container Disposal</i>	Empty packaging may be disposed along with normal builders waste via an authorised waste contractor.

14. TRANSPORT INFORMATION

<i>ADR/RID : Proper shipping name</i>	Not regulated under ADR/RID
<i>IMDG : Proper shipping name</i>	Not Regulated under IMDG
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

15. REGULATORY INFORMATION

<i>Risk Phrases</i>	None assigned.
<i>Safety Phrases</i>	None assigned. However the following are given as advisory. Do not breathe dust. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

16. OTHER INFORMATION

<i>First Issue Date</i>	22.02.1995
<i>Revisions Highlighted</i>	Composition/Information on the Components
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.
<i>UK Legislation</i>	Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions. Chemicals (Hazard Information and Packaging) Regulations, 2002. SI 1999/437: The Control of Substances Hazardous to Health Regulations SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.
<i>UK Guidance Publications</i>	General Approved Code of Practice to COSHH Regulations, HSE. EH40, Occupational Exposure Limits, HSE. Revised Annually. HS(G) 53, Respiratory Protective Equipment - a Practical Guide for Users, HSE. EH44, Dust in the Workplace: General Principles of Protection, HSE. HS(G) 37, An Introduction to Local Exhaust Ventilation, HSE.
<i>Footnote</i>	The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.