



## Sika Liquid Damp Proof Membrane Part A

Date of issue - 12/11/2002.

SKLDPMA

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product Code** SKLDPMA  
**Product Name** Sika Liquid Damp Proof Membrane Part A  
**Product Description** 2-component epoxy resin system.  
**Manufacturer/Supplier** Sika Limited  
Watchmead  
Welwyn Garden City  
Hertfordshire.  
AL7 1BQ  
tel. 01707 394444  
Fax. 01707 329129

**2. COMPOSITION/INFORMATION ON THE COMPONENTS****Preparation - Hazardous ingredients ( Europe )**

Component	CAS/EINECS	Concentration	Classification	Risk Phrases
Epoxy resin ( No.Av. mol.wt. < 700)	25068-38-6	25.00% - 50.00%	Xi, N	R36/38, R43, R51/53
Aliphatic glycidyl ether	68609-97-2	2.50% - 10.00%	Xi, N	R38, R43, R51/53
Solvent Naptha (petroleum) heavy aromatic.	64742-94-5	2.50% - 10.00%	Xn, N	R51/53, R65, R66

**3. HAZARD IDENTIFICATION**

**Main Hazards** Irritating to eyes and skin.  
May cause sensitisation by skin contact.  
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**4. FIRST AID MEASURES**

**Eye Contact** Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open.  
Obtain medical attention urgently.

**Skin Contact** Wipe off as much as possible with a clean dry cloth. Wash skin thoroughly with soap and water.  
If material proves difficult to remove, use suitable skin cleanser (not solvent).  
Solvents should not be used to clean skin because they may increase the penetration of the material.  
Contaminated clothing should be washed or dry-cleaned before re-use.

**Ingestion** Wash out mouth with water. Obtain medical attention.

**Inhalation** Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.

**5. FIRE FIGHTING MEASURES**

**Extinguishing Media** Not readily combustible.  
Use foam, dry chemical or carbon dioxide.

**Extinguishing Media - Not suitable** Do not use water jet.

**Special Hazards of Product** Combustion will produce smoke, carbon dioxide and carbon monoxide.

**Protective Equipment for Fire-Fighting** Wear full protective clothing and self-contained breathing apparatus.



## SAFETY DATA SHEET

### Sika Liquid Damp Proof Membrane Part A

Date of issue - 12/11/2002.

SKLDPMA

#### 6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

#### 7. HANDLING AND STORAGE

<i>Handling</i>	Use in well ventilated area. Avoid contact with eyes, skin and clothing.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Paste.
<i>Color</i>	Grey.
<i>Odor</i>	Faint. Characteristic.
<i>Flash Point °C</i>	112
<i>Solubility - Water</i>	Insoluble. 4% at 20 °C.
<i>Density (kg/m<sup>3</sup>)</i>	Approx. 1400 at 20 °C.
<i>Autoignition Temperature °C</i>	500
<i>Viscosity (at 20°C)</i>	Thixotropic paste

#### 10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Heating may produce: oxides of carbon. acrid smoke and irritating fumes.

#### 11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	Irritating to the eyes.
<i>Skin irritation</i>	Prolonged contact may cause irritation.
<i>Sensitization - Skin</i>	The low molecular weight epoxy resin is a potential skin sensitiser.



## SAFETY DATA SHEET

### Sika Liquid Damp Proof Membrane Part A

Date of issue - 12/11/2002.

SKLDPMA

#### 12. ECOLOGICAL INFORMATION

<i>Mobility</i>	The product is insoluble in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.


#### 13. DISPOSAL

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

#### 14. TRANSPORT INFORMATION

<i>UN : UN number</i>	3082
<i>UN : Proper shipping name</i>	Environmentally hazardous substances, liquid, n.o.s.
<i>UN : Class</i>	9
<i>UN : Packing Group</i>	3
<i>ADR/RID : Number</i>	3082
<i>ADR/RID : Proper shipping name</i>	Environmentally hazardous substance, liquid, n.o.s. contains Epoxy Resin
<i>ADR/RID : Class</i>	
<i>ADR/RID : Item Number</i>	11(c)
<i>ADR/RID : Hazard Identification Number</i>	90
<i>IMDG : Proper shipping name</i>	Environmentally hazardous substance, liquid, N.O.S. contains Epoxy Resin
<i>IMDG : Packing Group</i>	3
<i>IMDG : Class</i>	9
<i>IMDG : MFAG Number</i>	9028
<i>IATA : Proper shipping name</i>	Not hazardous for Air Transport

#### 15. REGULATORY INFORMATION

<i>Label Requirements</i>	Irritant, Dangerous for the environment 
<i>Risk Phrases</i>	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<i>Safety Phrases</i>	Avoid contact with skin. Wear suitable gloves.  Contains epoxy constituents. See information supplied by the manufacturer.



## SAFETY DATA SHEET

### Sika Liquid Damp Proof Membrane Part A

Date of issue - 12/11/2002.

SKLDPMA

#### 16. OTHER INFORMATION

<i>First Issue Date</i>	12.11.2002
<i>Revisions Highlighted</i>	Future revisions will incorporate such information as is required but which is not available at this time.
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.
<i>UK Legislation</i>	Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions. SI 2002/1689 Chemicals (Hazard Information and Packaging) Regulations, 2002. SI 1999/437: The Control of Substances Hazardous to Health Regulations SI No. 972/1996: The Special Waste Regulations 1996 SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.
<i>UK Guidance Publications</i>	Approved Code of Practice - Management of Health and Safety at Work, HSE. General Approved Code of Practice to COSHH Regulations, HSE.
<i>Footnote</i>	The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.



## Sika Liquid Damp Proof Membrane, Part B

Date of issue - 12/11/2002.

SKLDPMB

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product Code** SKLDPMB  
**Product Name** Sika Liquid Damp Proof Membrane, Part B  
**Product Description** 2-component epoxy resin based system.  
**Manufacturer/Supplier** Sika Limited  
Watchmead  
Welwyn Garden City  
Hertfordshire.  
AL7 1BQ  
tel. 01707 394444  
Fax. 01707 329129

**2. COMPOSITION/INFORMATION ON THE COMPONENTS**Preparation - Hazardous ingredients ( Europe )

Component	CAS/EINECS	Concentration	Classification	Risk Phrases
Benzyl Alcohol	100-51-6	10.00% - 25.00%	Xn	R20/22
Isophoronediamine	2855-13-2	2.50% - 10.00%	C	R21/22, R34, R43, R52/53
Triethylenetetramine	112-24-3	2.50% - 10.00%	C	R21, R34, R43, R52/53
2,4,6-Tri(dimethylaminomethyl) phenol	90-72-2	2.50% - 10.00%	Xn	R22, R36/38
Solvent Naptha (petroleum) heavy aromatic.	64742-94-5	2.50% - 10.00%	Xn, N	R51/53, R65, R66

**3. HAZARD IDENTIFICATION**

**Main Hazards** Causes burns.  
May cause sensitisation by skin contact.  
Harmful if swallowed.  
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**4. FIRST AID MEASURES**

**Eye Contact** Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open.  
Eyelids should be held away from the eyeball to ensure thorough rinsing.  
Obtain medical attention urgently.

**Skin Contact** Wipe off as much as possible with a clean dry cloth.  
Wash skin thoroughly with soap and water.  
If material proves difficult to remove, use suitable skin cleanser (not solvent).  
Solvents should not be used to clean skin because they may increase the penetration of the material.  
Contaminated clothing should be washed or dry-cleaned before re-use.

**Ingestion** Do not induce vomiting.  
Obtain medical attention.

**Inhalation** Remove from exposure.  
In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.



# SAFETY DATA SHEET

## Sika Liquid Damp Proof Membrane, Part B

Date of issue - 12/11/2002.

SKLDPMB

### 5. FIRE FIGHTING MEASURES

<i>Extinguishing Media</i>	Not readily combustible. Use foam, dry chemical or carbon dioxide.
<i>Extinguishing Media - Not suitable</i>	Do not use water jet.
<i>Special Hazards of Product</i>	Thermal decomposition or burning may release oxides of carbon, nitrogen and other toxic gases and vapours.
<i>Protective Equipment for Fire-Fighting</i>	Wear full protective clothing and self-contained breathing apparatus.

### 6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

### 7. HANDLING AND STORAGE

<i>Handling</i>	Mix in a well ventilated area. Avoid contact with eyes, skin and clothing.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed. Keep away from foodstuffs

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Paste.
<i>Color</i>	Brown.
<i>Odor</i>	Ammoniacal.
<i>pH</i>	Approx. 11 in water. (soluble phase)
<i>Flash Point °C</i>	102
<i>Solubility - Water</i>	Partially soluble. (40%)
<i>Density (kg/m<sup>3</sup>)</i>	Approx. 1400 at 20 °C.
<i>Viscosity (at 20°C)</i>	Thixotropic paste



# SAFETY DATA SHEET

## Sika Liquid Damp Proof Membrane, Part B

Date of issue - 12/11/2002.

SKLDPMB

### 10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Heating may produce: ammonia. oxides of carbon. oxides of nitrogen. acrid smoke and irritating fumes.

### 11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	This material is corrosive to the eye.
<i>Skin irritation</i>	This material is corrosive to the skin.
<i>Sensitization - Skin</i>	The possibility of allergic sensitisation should be considered.

### 12. ECOLOGICAL INFORMATION

<i>Mobility</i>	A major part of the product will dissolve slowly in water.
<i>Persistence/degradability</i>	The product is expected to be partially or slowly biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.

### 13. DISPOSAL

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

### 14. TRANSPORT INFORMATION

<i>UN : UN number</i>	1759
<i>UN : Proper shipping name</i>	Corrosive solid, n.o.s.
<i>UN : Class</i>	8
<i>UN : Packing Group</i>	3
<i>ADR/RID : Number</i>	1759
<i>ADR/RID : Proper shipping name</i>	Corrosive solid, N.O.S.
<i>ADR/RID : Class</i>	contains Triethylenetetramine
<i>ADR/RID : Item Number</i>	65(c)
<i>ADR/RID : Hazard Identification Number</i>	80
<i>IMDG : Proper shipping name</i>	Corrosive liquid, N.O.S. contains Triethylenetetramine
<i>IMDG : Packing Group</i>	3
<i>IMDG : Class</i>	8
<i>IMDG : Ems Number</i>	8-15
<i>IATA : Proper shipping name</i>	Corrosive solid, N.O.S. contains Triethylenetetramine
<i>IATA : Packing Group</i>	3
<i>IATA : Class</i>	8



# SAFETY DATA SHEET

## Sika Liquid Damp Proof Membrane, Part B

Date of issue - 12/11/2002.

SKLDPMB

### 15. REGULATORY INFORMATION

#### *Label Requirements*

Corrosive



#### *Risk Phrases*

Causes burns.  
Harmful if swallowed.  
May cause sensitisation by skin contact.  
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### *Safety Phrases*

Avoid contact with skin.  
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Wear suitable protective clothing, gloves and eye/face protection.  
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

### 16. OTHER INFORMATION

#### *First Issue Date*

12.11.2002

#### *Revisions Highlighted*

Future revisions will incorporate such information as is required but which is not available at this time.

#### *Uses and Restrictions*

Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.

#### *UK Legislation*

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.  
SI 2002/1689: Chemicals (Hazard Information and Packaging) Regulations, 2002.  
SI 1999/437: The Control of Substances Hazardous to Health Regulations  
SI No. 972/1996: The Special Waste Regulations 1996  
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

#### *UK Guidance Publications*

Approved Code of Practice - Management of Health and Safety at Work, HSE.  
General Approved Code of Practice to COSHH Regulations, HSE.

#### *Footnote*

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.