



Sika® SprayGard®

Protection for Concrete Mixers

Technical Data Sheet

DESCRIPTION

Sika SprayGard is a blend of selected oils and compounds designed to protect valuable concrete mixing equipment.

Sika SprayGard provides protection to mixing and transport equipment by creating a barrier between the steel and fresh concrete. **Sika SprayGard** also assists in removing any old hardened concrete build up.

USES

All mixing and transporting equipment in contact with fresh concrete.

ADVANTAGES

- * Provides a protective coating to eliminate concrete adhering to component surfaces.
- * Neutralises the corrosive action of cement on metal parts.
- * Reduces expensive downtime by eliminating removal on hardened concrete.
- * Easy to apply and use.

Technical Data (typical)

Form:	Liquid
Colour:	Opaque
Specific gravity:	0.885
Closed flash point:	200°C
Kinematic Viscosity @40°C:	31 cst

All above values are approximate.



METHOD OF USE

Sika SprayGard should be spray applied over the equipment at least once a week.

IMPORTANT NOTES


Please adhere to the advice given in the MSDS.

PACKAGING

Sika SprayGard is supplied in 25 litre drums, 200 litre drums and in bulk.

STORAGE AND SHELF LIFE

Minimum 1 year in sealed containers stored in dry warehouse condition (+5°C - +25°C). Protect from frost.



Handling Precautions

Sika products are generally harmless provided that certain precautions normally taken when handling chemicals are observed. The materials must not, for instance, be allowed to come in contact with foodstuffs or food utensils and measures should also be taken to prevent the uncured materials from coming in contact with the skin, since people with particularly sensitive skin may be affected. The use of protective clothing, goggles, barrier creams and rubber gloves is required. The skin should be thoroughly cleaned at the end of each working period either by washing with soap and warm water or by using a resin-removing cream - the use of powerful solvents is to be avoided. Disposable paper towels - not cloth towels - should be used to dry the skin. Adequate ventilation of the working area is recommended. In case of accidental eye or mouth contact, flush with water - consult a doctor immediately. Health and Safety information on Sika Products is available and we strongly advise that this is read prior to their use. Sika products are for professional use and should be stored in sealed containers away from the reach of children.

Important Note

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Please consult our Technical Sales Department for further information

SIKA LIMITED

Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ

Tel: 01707 394444 Email: sika@uk.sika.com

Fax: 01707 329129 www.sika.com

